



MATERIAL SAFETY DATA SHEET (MIXED REFRIGERANT R410A)

MSDS for the Blend and Individual Components

Information in this format is provided as a service to our customers and is intended only for their use. Others may use it at their own discretion and risk. This information is based upon technical information. Believes to be reliable. It is subject to revision as additional knowledge and experience are gained.

CHEMICAL PRODUCT/COMPANY IDENTIFICATION

Product Identification: Mixed Refrigerant (R125+R32)

R410a is a product of refrigerant mixed of 50% R125 and 50% R32

Formula: CF_3CHF_2/CF_2H_2

COMPANY IDENTIFICATION

DISTRIBUTOR

EA BROTHERS CO. LTD

Plot No:302, Block A-1 Tabata Road, Tabata Dar Es Salaam

www.eabrothers.co.tz

COMPOSITION/INFORMATION ON INGREDIENTS

Components:	
Material	CAS Number
R125/R32	
PENTAFLUOROETHANE (R125)	354-33-6
THERMODYNAMIC (R32)	75-10-5
PHYSICAL AND CHEMICAL PROPERTIES	
Physical Data	
Molecular weight:	72.58g/mol
Boiling Point of Saturated Liquid:	-51.53°C
Critical Pressure:	4.926MPa
Critical temperature:	72.13°C
Form:	Liquefied Gas
Color:	Clear, Colorless



ABBACOOOL REFRIGERANTS

FIRE FIGHTING MEASURES

Flammable Properties

Flash Point: Not applicable

Fire and Explosion Hazards:

Cylinders may rupture under fire conditions. Decomposition may occur forming toxic gases.

Extinguishing Media:

Use media appropriate for surrounding material.

Fire Fighting Instructions

Cool tank/container with water spray. Self-contained breathing apparatus (SCBA) may be required if cylinders rupture or release under fire conditions.

HAZARDS IDENTIFICATION

Potential Health Effects

Inhalation of high concentrations of vapor is harmful and may cause heart irregularities, unconsciousness, or death. Intentional misuse or deliberate inhalation may cause death without warning. Vapor reduces oxygen available for breathing and is heavier than air. Liquid contact can cause frostbite.

Human Health Effects

Skin contact may cause frostbite from exposure to the liquid. Inhalation may include nonspecific discomfort, such as nausea, headache, or weakness; or temporary nervous system depression with anesthetic effects such as dizziness, headache, confusion, incoordination, and loss of consciousness.

Higher exposures to vapours may lead to these effects: temporary lung irritation effects with cough, discomfort, difficulty breathing or shortness of breath; temporary alteration of the heart's electrical activity with irregular pulse, palpitations, or inadequate circulation, abnormal kidney function as detected by laboratory tests or fatality from gross overexposure. Individuals with pre-existing diseases of the central nervous system, cardiovascular system, lungs or kidneys may have increased susceptibility to the toxicity of excessive exposures.



FIRST AID MEASURES

First Aid

INHALATION

If high concentrations are inhaled, immediately remove to fresh air. Keep person calm. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

SKIN CONTACT

Flush skin with water for at least 15 minutes after excessive contact. Seek medical assistance if irritation is present. Wash contaminated clothing before reuse. Treat for frostbite if necessary, by gently warming affected area.

EYE CONTACT

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

INGESTION

Ingestion is not considered a potential route of exposure.

Notes to Physicians

Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should only be used with special caution in situations of emergency life support.

ACCIDENTAL RELEASE MEASURES

Safeguards (Personnel)

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean up. Ventilate area, especially low or enclosed places where heavy vapours might collect. Remove open flames. Use self-contained breathing apparatus (SCBA) if large spill or leak occurs. Spill Clean Up Comply with Federal, State and local regulations for reporting releases.

HANDLING AND STORAGE

Handling (Personnel)

Avoid breathing vapours or mist. Avoid contact with eyes or skin. Use with sufficient ventilation to keep employee exposure below recommended limits. Storage Store in a clean, dry place. Do not heat above 52 °C(126°F).



ABBACOOOL REFRIGERANTS

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls

Use sufficient ventilation to keep employee exposure below recommended limits. Local exhaust should be used when large amounts are released. Mechanical ventilation should be used in low or enclosed places. Refrigerant concentration monitors may be necessary to determine vapor concentrations in work areas prior to use of torches or other open flames, or if employees are entering enclosed areas.

Personal Protective Equipment

Lined butyl gloves should be used to avoid prolonged or repeated exposure. Chemical splash goggles should be available for use as needed to prevent eye contact.

Fire protective clothing (NOMEX) with antistatic control should be worn when handling this product. Under normal manufacturing conditions, no respiratory protection is required when using this product. Self-contained breathing apparatus (SCBA) is required if a large release occurs.

STABILITY AND REACTIVITY

Chemical Stability

Stable

Conditions to Avoid

Avoid open flames and high temperatures.

Incompatibility with Other Materials

Incompatible with alkali or alkaline earth metals - powdered Al,Zn, Be, etc.

Decomposition

Decomposition products are hazardous.

This material can be decomposed by high temperatures (open flames, glowing metal surfaces, etc.) forming hydrofluoric and hydrofluoric acids, and possibly carbonyl halides.

Polymerization

Polymerization will not occur.

TOXICOLOGICAL INFORMATION

General LC50/1h (ppm) LD50(Rat)-Ingestion of 7340 mg/kg.



ECOLOGICAL INFORMATION

General

Product is persistent in air (atmospheric lifetime: 14years.)

Product is not significant hazardous for the aquatic environment as:

Considerable volatility. No bioaccumulation.

DISPOSAL CONSIDERATIONS

General

Comply with local and national regulations. Contact the producer for recycling. To avoid treatment, as far as possible, use dedicated containers.

TRANSPORTATION INFORMATION

Shipping Information

DOT/IMO

2.2

Proper Shipping Name:

MIXED REFRIGERANT

UN No.:

(PENTAFLUOROETHANE AND THERMODYNAMIC)

Shipping Containers

3163

Tank Cars, Cylinders Ton,
Tanks, 11.3kg cylinder



REGULATORY INFORMATION

Number in Annex

Not dangerous according to Dir. 88/EEC.

EC Classification

-Symbol

-Labelling of cylinders

Labelling "Dangerous for environment" not classified in the absence of classification to be applied to dangerous preparations.

-Risk phases

-EEC Hazard Class

OTHER INFORMATION

This information is only for reference.

The data in this Material Safety Data Sheet only to the specific material designated herein and does not relate to use in combination with any other material or in any process.